

Cooper Endeavor tire specifications table

Tire Size	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tire Weight	Max Load	Tread Depth
185/65R15	680 A A	STD	BLK	5-6.5	5.5	7.4	24.45	17	1235	10.5
195/60R15	680 A A	STD	BLK	5.5-7	6	7.9	24.21	18	1235	10.5
195/65R15	680 A A	STD	BLK	5.5-7	6	7.9	25	18	1356	10.5
205/50R17	680 A A	XL	BLK	5.5-7.5	6.5	8.4	25.12	22	1433	10.5
215/45R17	680 A A	XL	BLK	7-8	7	8.4	24.69	21	1356	10.5
215/50R17	680 A A	XL	BLK	6-7.5	7	8.9	25.51	23	1521	10.5
225/45R18	680 A A	XL	BLK	7-8.5	7.5	8.9	25.94	24	1521	10.5
225/50R17	680 A A	XL	BLK	6-8	7	9.2	25.91	22	1653	10.5
235/40R19	680 A A	XL	BLK	8-9.5	8.5	9.5	26.42	26	1565	10.5
235/45R18	680 A A	STD	BLK	7.5-9	8	9.3	26.34	25	1477	10.5
235/50R17	680 A A	STD	BLK	6.5-8.5	7.5	9.6	26.3	24	1565	10.5
205/55R16	680 A A	STD	BLK	5.5-7.5	6.5	8.4	24.88	19	1356	10.5
205/60R16	680 A A	STD	BLK	5.5-7.5	6	8.2	25.67	20	1389	10.5
205/65R16	680 A A	STD	BLK	5.5-7.5	6	8.2	26.46	20	1521	10.5
215/55R16	680 A A	XL	BLK	6-7.5	7	8.9	25.28	22	1609	10.5
215/55R17	680 A A	STD	BLK	6-7.5	7	8.7	26.34	21	1477	10.5
215/60R16	680 A A	STD	BLK	6-7.5	6.5	8.7	26.14	20	1521	10.5
225/45R17	680 A A	STD	BLK	7-8.5	7.5	8.9	24.96	24	1356	10.5
225/60R16	680 A A	STD	BLK	6-8	6.5	9	26.61	22	1653	10.5
225/65R16	680 A A	STD	BLK	6-8	6.5	9	27.48	23	1764	10.5
215/70R15	680 A A	STD	BLK	5.5-7	6.5	8.7	26.89	22	1653	10.5
245/45R18	680 A A	XL	BLK	7.5-9	8	9.6	26.65	26	1764	10.5

