

Evolution M/T tire specifications table

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tire Weight	Max Load	Tread Depth
31X10.50 R15LT	109Q		C	OWL	7 - 9	8.5	10.9	30.63	45	2270	19
33X12.50 R15LT	108Q		C	OWL	8.5 - 11	10	12.1	32.83	56	2205	20
35X12.50 R15LT	113Q		C	OWL	8.5 - 11	10	12.2	34.72	61	2535	20
LT265/75 R16	123\120Q		E	OWL	7 - 8	7.5	10.1	31.73	49	3415	18.5
LT285/75 R16	126\123Q		E	OWL	7.5 - 9	8	11.3	32.83	55	3750	18.5
LT265/70 R17	121\118Q		E	OWL	7 - 8.5	8	10.8	31.73	51	3195	18.5
LT285/70 R17	121\118Q		E	OWL	7.5 - 9	8.5	11.5	32.91	57	3195	18.5
LT295/70 R17	121\118Q		E	OWL	7.5 - 10	8.5	11.8	33.46	59	3195	19.5
35X12.50 R17LT	121Q		E	OWL	8.5 - 11	10	12.7	34.76	64	3195	20
LT275/70 R18	125\122Q		E	OWL	7 - 8.5	8	11	33.31	55	3640	19
LT295/70 R18	129\126Q		E	BLK	7.5 - 10	8.5	12	34.25	61	4080	19.5
35X12.50 R20LT	121Q		E	BLK	8.5 - 11	10	12.5	34.69	65	3195	20