

Cooper® Cobra Instinct™ tire specifications table

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Section Width	Overall Diameter	Max Load	Tread Depth
215/45ZR17	91W	500 AA A	XL	VSB	7 - 8	215	24.7	1356	10
225/45ZR17	94W	500 AA A	XL	VSB	7.5 - 8.5	225	25	1477	10
245/45ZR17	99W	500 AA A	XL	VSB	8 - 9	245	25.7	1709	10
225/40ZR18	92Y	500 AA A	XL	VSB	8 - 9	225	25.1	1389	10
225/45ZR18	95Y	500 AA A	XL	VSB	7.5 - 8.5	225	25.9	1521	10
235/40ZR18	95Y	500 AA A	XL	VSB	8.5 - 9.5	235	25.4	1521	10
245/40ZR18	97Y	500 AA A	XL	VSB	8.5 - 9.5	245	25.7	1609	10
245/45ZR18	100Y	500 AA A	XL	VSB	8 - 9	245	24.7	1764	10
255/40ZR18	99Y	500 AA A	XL	VSB	9 - 10	255	27	1709	10
255/35ZR18	94Y	500 AA A	XL	VSB	9 - 10	255	25	1477	10
225/40ZR19	93Y	500 AA A	XL	VSB	8 - 9	225	26.1	1433	10
225/45ZR19	96W	500 AA A	XL	VSB	7.5 - 8.5	225	27	1565	10
235/35ZR19	91Y	500 AA A	XL	VSB	8.5 - 9.5	235	25.5	1356	10
245/35ZR19	93Y	500 AA A	XL	VSB	8.5 - 9.5	245	25.8	1433	10
245/40ZR19	98Y	500 AA A	XL	VSB	8.5 - 9.5	245	26.7	1653	10
245/45ZR19	102Y	500 AA A	XL	VSB	8 - 9	245	25.1	1874	10
255/35ZR19	96Y	500 AA A	XL	VSB	9 - 10	255	25.9	1565	10
255/40ZR19	100Y	500 AA A	XL	VSB	9 - 10	255	25.5	1764	10
275/35ZR19	100Y	500 AA A	XL	VSB	9.5 - 11	275	25.8	1764	10
285/35ZR19	99Y	500 AA A	SL	VSB	10 - 11	285	27.7	1709	10
245/40ZR20	99Y	500 AA A	XL	VSB	8.5 - 9.5	245	27.7	1709	10
245/45ZR20	103Y	500 AA A	XL	VSB	8 - 9	245	26.1	1929	10

275/40ZR20	106Y	500 AA A	XL	VSB	9.5 - 11	275	26.7	2094	10
------------	------	----------	----	-----	----------	-----	------	------	----

265/35ZR20	99Y	500 AA A	XL	VSB	9.5 - 10.5	265	25.4	1709	10
------------	-----	----------	----	-----	------------	-----	------	------	----

275/35ZR20	102Y	500 AA A	XL	VSB	9.5 - 11	275	25.7	1874	10
------------	------	----------	----	-----	----------	-----	------	------	----
